

subwoofer piatto 240 W - flat subwoofer 240W



Rifiniture Finishes

Tattamento aggrappante per tinteggiatura
Grip treatment for painting (Standard)



WAE220E

Laccato in tutti i colori RAL (su richiesta)
Lacquered in all RAL colours (on request)



WAE220C

Acciaio inox satinato (su richiesta)
Satin stainless steel (on request)



WAX220S

Acciaio inox lucido (su richiesta)
Polished stainless steel (on request)



WAX220L

Materiale cabinet
Cabinet material

WAE220E - WAE220C legno
WAX120S - WAX120L contenitore esterno in acciaio inox, struttura interna legno

WAE220E - WAE220C wood
WAX220S - WAX220L stainless steel external housing, wooden internal structure

Tipo
Type

Subwoofer attivo alta escursione
High excursion, active subwoofer

Componenti
Components

Magnete al neodimio, cestello in alluminio
Neodymium magnet, aluminum basket

Potenza RMS
Power RMS (W)

240

Potenza Massima
Max Power (W)

480

Risp. in frequenza
Frequency response (Hz)

33 - 150

Auto accensione / spegnimento
Auto power on/off



Subwoofer (cm)

2 x 20,0

Dimensioni
Dimensions H x W x D (cm)

WAE220E - WAE220C = 40,0 x 60,0 x 18,0
WAX220S - WAX220L = 36,6 x 56,6 x 16,3

Peso (Kg)
Weight (Kg)

WAE220E - WAE220C = 18,0
WAX220S - WAX220L = 17,0

Kit fissaggio a parete - Wall mount kit



Codice - Code

HTF004